

((12) United States Patent Dreyer

(10) Patent No.:

US 6,527,097 B2

(45) Date of Patent:

Mar. 4, 2003

(54)	CONVEYOR IDLER					
(75)	Inventor:	Tertius F. Dreyer, Benoni (ZA)				
(73)	Assignee:	Rollerbrak (Proprietary) Limited, Heidelberg (ZA)				
(*)	Notice:	Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.				
(21)	Appl. No.:	09/999,181				
(22)	Filed:	Dec. 3, 2001				
(65)) Prior Publication Data					
US 2002/0066648 A1 Jun. 6, 2002						
	Rel	ated U.S. Application Data				
(63)	Continuation-in-part of application No. PCT/IB00/01571, filed on Oct. 31, 2000.					
(30)	Foreign Application Priority Data					
Nov	. 2, 1999	(ZA) 99/6862				
(51)	Int. Cl.7	B65G 13/00				
. ,		193/35 A; 193/37; 193/35 R				
(58) Field of Search						
	1	93/37, 35 R; 198/781.01, 781.02, 781.03, 781.04, 577				
(56)		References Cited				
U.S. PATENT DOCUMENTS						
	116,413 A	* 6/1871 Close 192/45				

836,097 A * 11/1906 Dann 192/45

842,841 A * 1/1907 Start 188/69

897,846 A * 9/1908 Olds 192/45 1,273,952 A * 7/1918 Tibbetts 192/113.1

1,437,718	Α		12/1922	Burns
2,060,376	Α	*	11/1936	Jex 188/30
2,085,271	Α	*	6/1937	Pfluger 192/105 CD
2,769,515	Α	*	11/1956	Thomas et al 192/45
3,012,645	Α	*	12/1961	Gensheimer 192/45
3,209,880	Α	*	10/1965	Dietiker 193/32
3,312,320	Α	*	4/1967	Froio 193/35 A
3,685,621	Α	*	8/1972	Gulick et al 192/12 B
3,713,521	Α	*	1/1973	Moritake 188/161
3,899,063	Α	*	8/1975	Pollard 188/130
3,918,561	Α	*	11/1975	Isacsson 188/184
4,548,316	Α	*	10/1985	Maurer 192/48.92
5,147,020	Α	*	9/1992	Scherman et al 188/382
5,253,856	Α	*	10/1993	Fuchi et al 198/570
6,131,717	Α	*	10/2000	Owen 188/82.1

FOREIGN PATENT DOCUMENTS

1/1953

5/1983

DE 864 978 C DE 32 45 347 A

* cited by examiner

Primary Examiner-Christopher P. Ellis Assistant Examiner-Richard Ridley (74) Attorney, Agent, or Firm-Nixon & Vanderhye, PC

ABSTRACT

A conveyor idler includes a sleeve having an outer surface and an inner surface, a shaft about which the sleeve can rotate in a forward direction, a locking mechanism for preventing the sleeve from rotating in a reverse direction, but which locking mechanism permits rotation of the sleeve in the forward direction, the locking mechanism being located within the sleeve and having a shaft member fixed to the shaft, with at least one locking member which can move between an unlocked position in which the sleeve can rotate in the forward direction and a locked position in which the locking member locks the sleeve to the shaft member to prevent rotation of the sleeve in the reverse direction.

18 Claims, 10 Drawing Sheets

